
INVENTOR'S NAME: Brett L. Williams

SERIAL NO.: 09/510,375 DOCKET NO.: 303.164US3





OE ·

42

**LATCHES** 

FIG. 1

TITLE: SYSTEM SUPPORTING MULTIPLE MEMORY MODES INCLUDING A BURST EXTENDED DATA OUT MODE

INVENTOR'S NAME: Brett L. Williams
SERIAL NO.: 09/510,375 DOCKET NO.: 303.164US3

Burst	Starting Column Address						
Length	$A_2$	A <sub>1</sub>	A <sub>0</sub>	Linear	Interleave		
2	٧	V	0	0-1	0-1		
	٧	٧	1	1-0	1-0		
4	٧	0	0	0-1-2-3	0-1-2-3		
	<b>V</b>	0	1	1-2-3-0	1-0-3-2		
	>	1	0	2-3-0-1	2-3-0-1		
	>	1	1	3-0-1-2	3-2-1-0		
8	0	0	0	0-1-2-3-4-5-6-7	0-1-2-3-4-5-6-7		
	0	0	1	1-2-3-4-5-6-7-0	1-0-3-2-5-4-7-6		
	0	1	0	2-3-4-5-6-7-0-1	2-3-0-1-6-7-4-5		
	0	1	1	3-4-5-6-7-0-1-2	3-2-1-0-7-6-5-4		
	1	0	0	4-5-6-7-0-1-2-3	4-5-6-7-0-1-2-3		
	1	0	1	5-6-7-0-1-2-3-4	5-4-7-6-1-0-3-2		
	1	1	0	6-7-0-1-2-3-4-5	6-7-4-5-2-3-0-1		
	1	1	1	7-0-1-2-3-4-5-6	7-6-5-4-3-2-1-0		

FIG. 2

TITLE: SYSTEM SUPPORTING MULTIPLE MEMORY MODES INCLUDING A BURST EXTENDED DATA OUT MODE

INVENTOR'S NAME: Brett L. Williams

SERIAL NO.: 09/510,375 DOCKET NO.: 303.164US3






FIG. 3





ME

뗑


g

RAS

CAS

INVENTOR'S NAME: Brett L. Williams

SERIAL NO.: 09/510,375 DOCKET NO.: 303.164US3








FIG. 7

PIN#	SYMBOL	PIN#	SYMBOL	PIN#	SYMBOL	PIN#	SYMBOL
1	Vss	19	A10	37	NC	55	DQ12
2	DQ1	20	DQ5	38	NC	56	DQ28
3	DQ17	21	DQ21	39	Vss	57	DQ13
4	DQ2	22	DQ6	40	CAS0	58	DQ29
5	DQ18	23	DQ22	41	CAS2	59	Vcc
6	DQ3	24	DQ7	42	CAS3	60	DQ30
7	DQ19	25	DQ23	43	CAS1	61	DQ14
8	DQ4	26	DQ8	44	RAS0	62	DQ31
9	DQ20	27	DQ24	45	RAS1	63	DQ15
10	Vcc	28	A7	46	ŌE	64	DQ32
11	PD5	29	NC	47	WE	65	DQ16
12	A0	30	Vcc	48	PD ECC	66	PD EDO
13	A1	31	<b>A8</b>	49	DQ9	67	PD1
14	A2	32	<b>A</b> 9	50	DQ25	68	PD2
15	А3	33	NC	51	DQ10	69	PD3
16	A4	34	NC	52	DQ26	70	PD4
17	A5	35	NC	53	DQ11	71	PD refresh
18	<b>A</b> 6	36	NC	54	DQ27	72	Vss

FIG. 8



SERIAL NO.: 09/510,375 DOCKET NO.: 303.1640S3 REPLACEMENT SHEET



REPLACEMENT SHEET

